





INNOVATION

Complete Manufactured using Bergstrom's engineering, design and World class development manufacturing capabilities. systems and

QUALITY

Designed, engineered and manufactured in the U.S. and China facilities.

MANUFACTURING

processes.

Suggested Applications



















www.bergstrominc.com









Rockford, U.S.A. **** + 1 - 815-874-7821

Europe

Wales, United Kingdom **L** + 44 - 144-386-212

Madrid, Spain

\(+ 34 - 918-775-840

Asia-Pacífic

Changzhou, Jiangsu, China **\(+** 86 - 519-511-7821







Main Features:

Electrified variable speed compressor with brushless motor for improved efficiency and reliability.

Brazed plate evaporator to provide secondary loop cooling.

Brazed plate condenser to provide secondary loop heating/defrost.

Coolant pumps and valves provide coolant flow control.

Mixing valves for temperature control of secondary loop fluid and modes.

Thermal management of components and cabin for conventional and zero-emission vehicles.

TECHNICAL SPECIFICATIONS

| Cooling Capacity | 2.000 to 5.500 W |
|--------------------|----------------------------|
| (48V) | 6.824 to 18.767 BTU/hr |
| Heating Capacity | 2.000 to 5.000 W |
| (48V) | 6.824 to 17.061 BTU/hr |
| COP | 2.5 to 4.0 |
| Compressor Options | 24V, 48V, 400V, 600V, 800V |

| WEIGHT & DIMENSIONS | |
|---------------------------|---|
| Weight | 31,75 kg 70 lb |
| Dimensions (L x W x H) | 863 x 438 x 289 mm 34 x 17.2 x 11.4 in |



SYSTEM DIAGRAMS



